

MSBCCL112M-4 4KW 400/690V B3

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL112M-4 4KW 400/690V B3
Brand BUSCK
Item number B3041121

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	4	50	8,17	1440
690	4	50	4,7	1440
460	4,6	60	8,17	1728


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 26,71
Starting torque ratio 2,2
Pull up torque ratio 1,5
Pull out torque ratio 2,2
Starting current ratio 7

Efficiency class EFF2
Efficiency, load 100% 84,2
Power fact, load 100% 0,83

Painting Standard
Color RAL 9005
Weight kg 39
Sound pressure Lp dB(A) 65
Bearing DE 6306-2Z/C3
Bearing NDE 6206-2Z/C3
Balance grade Normal
Inertia kgm² 0,0107
Cable entries 2xM25

Brake torque, Nm 60



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no