

MSBCCL132S-4 5,5KW 400/690V B34

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL132S-4 5,5KW 400/690V B34
Brand BUSCK
Item number B3041325

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	11,03	1450
690	5,5	50	6,34	1450
460	6,33	60	11,03	1740



Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 36,22
Starting torque ratio 2,2
Pull up torque ratio 1,4
Pull out torque ratio 2,2
Starting current ratio 7

Efficiency class EFF2
Efficiency, load 100% 85,7
Power fact, load 100% 0,84

Painting Standard
Color RAL 9005
Weight kg 49
Sound pressure Lp dB(A) 71
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Inertia kgm² 0,023
Cable entries 2xM25

Brake torque, Nm 80



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no