

MSBCCL71A-6 0,18KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL71A-6 0,18KW 230/400V B3
Brand BUSCK
Item number B3060711

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,18	50	1,22	880
400	0,18	50	0,70	880
460	0,21	60	0,70	1056



Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 1,95
Starting torque ratio 1,6
Pull up torque ratio 1,5
Pull out torque ratio 1,7
Starting current ratio 4

Efficiency class EFF2
Efficiency, load 100% 56
Power fact, load 100% 0,70

Painting Standard
Color RAL 9005
Weight kg 0
Sound pressure Lp dB(A) 52
Bearing DE 6202-2Z/C3
Bearing NDE 6202-2Z/C3
Balance grade Normal
Cable entries 1xM20

Brake torque, Nm 4



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no