

T2AB71B-6 0,37KW 230/400V B5

Three-phase asynchronous brake motor in aluminum

Motor type T2AB71B-6 0,37KW 230/400V B5
Brand BUSCK
Item number B3060732e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	2,09	905
400	0,37	50	1,2	905
460	0,43	60	1,2	1086

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	67,6
Insulation class	F	Efficiency, load 75%	66,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	60,7
Max. ambient temp.	40°C	Power fact, load 100%	0,66
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	7
Starting torque ratio	2,4	Sound pressure Lp dB(A)	54
Pull up torque ratio	2,3	Bearing DE	6202 2RZ C3
Pull out torque ratio	2,5	Bearing NDE	6202 2RZ C3
Starting current ratio	3,3	Balance grade	Normal
Note	Brake motor IE2	Inertia kgm2	0,00115
		Brake torque, Nm	6

