

MSBCCL90S-6 0,75KW 230/400V B14

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL90S-6 0,75KW 230/400V B14
 Brand BUSCK
 Item number B3060903

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	3,79	920
400	0,75	50	2,18	920
460	0,86	60	2,18	1104


Duty S1
 Enclosure IP55
 Insulation class F
 Cooling IC411 (TEFC)
 Max. ambient temp. 40°C
 Min. ambient temp. -20°C
 Max. temp. rise 80 K
 Max altitude, masl 1000

Torque, Nm 7,8
 Starting torque ratio 2,2
 Pull up torque ratio 1,5
 Pull out torque ratio 2,2
 Starting current ratio 5,5

Efficiency class EFF2
 Efficiency, load 100% 69
 Power fact, load 100% 0,72

Painting Standard
 Color RAL 9005
 Weight kg 14
 Sound pressure Lp dB(A) 59
 Bearing DE 6205-2Z/C3
 Bearing NDE 6205-2Z/C3
 Balance grade Normal
 Cable entries 1xM20

Brake torque, Nm 20



BUSCK
www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
info@busck.no