

T2AB80B-8 0,25KW 230/400V B5

Three-phase asynchronous brake motor in aluminum

Motor type T2AB80B-8 0,25KW 230/400V B5
Brand BUSCK
Item number B3080812e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,25	50	1,58	700
400	0,25	50	0,91	700
460	0,29	60	0,91	840

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000


Starting torque ratio 2,1
Pull up torque ratio 2
Pull out torque ratio 2,5
Starting current ratio 3,5

Note Brake motor IE2

Efficiency class IE2
Efficiency, load 100% 66,9
Efficiency, load 75% 61,9
Efficiency, load 50% 57,7
Power fact, load 100% 0,59

Painting Standard
Color RAL 9005
Weight kg 11,21
Sound pressure Lp dB(A) 52
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm2 0,002322554

Brake torque, Nm 8



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no