

T2AB90S-8 0,37KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type T2AB90S-8 0,37KW 230/400V B3
Brand BUSCK
Item number B3080901e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	2,47	710
400	0,37	50	1,42	710
460	0,43	60	1,42	852

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	65
Insulation class	F	Efficiency, load 75%	62,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	54,8
Max. ambient temp.	40°C	Power fact, load 100%	0,58
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	14,76
Starting torque ratio	1,7	Sound pressure Lp dB(A)	56
Pull up torque ratio	1,6	Bearing DE	6205-2Z/C3
Pull out torque ratio	2,2	Bearing NDE	6205-2Z/C3
Starting current ratio	3,2	Balance grade	Normal
		Inertia kgm2	0,003265642
Note	Brake motor IE2	Cable entries	1xM20
		Brake torque, Nm	16

