

T2AB90S-8 0,37KW 230/400V B35

Three-phase asynchronous brake motor in aluminum

Motor type T2AB90S-8 0,37KW 230/400V B35
Brand BUSCK
Item number B3080904e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	2,47	710
400	0,37	50	1,42	710
460	0,43	60	1,42	852

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Starting torque ratio 1,7
Pull up torque ratio 1,6
Pull out torque ratio 2,2
Starting current ratio 3,2

Note Brake motor IE2

Efficiency class IE2
Efficiency, load 100% 65
Efficiency, load 75% 62,2
Efficiency, load 50% 54,8
Power fact, load 100% 0,58

Painting Standard
Color RAL 9005
Weight kg 14,76
Sound pressure Lp dB(A) 56
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,003265642
Cable entries 1xM20

Brake torque, Nm 16

