

T2AB90L-8 0,55KW 230/400V B35

Three-phase asynchronous brake motor in aluminum

Motor type T2AB90L-8 0,55KW 230/400V B35
 Brand BUSCK
 Item number B3080914e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,55	50	3,67	705
400	0,55	50	2,11	705
460	0,63	60	2,11	846

Duty S1
 Enclosure IP55
 Insulation class F
 Cooling IC411 (TEFC)
 Max. ambient temp. 40°C
 Min. ambient temp. -20°C
 Max. temp. rise 80 K
 Max altitude, masl 1000

Starting torque ratio 1,9
 Pull up torque ratio 1,7
 Pull out torque ratio 2,3
 Starting current ratio 3,4

Note Brake motor IE2

Efficiency class IE2
 Efficiency, load 100% 65
 Efficiency, load 75% 62,6
 Efficiency, load 50% 55,6
 Power fact, load 100% 0,58

Painting Standard
 Color RAL 9005
 Weight kg 17,32
 Sound pressure Lp dB(A) 56
 Bearing DE 6205-2Z/C3
 Bearing NDE 6205-2Z/C3
 Balance grade Normal
 Inertia kgm² 0,004281097
 Cable entries 1xM20

Brake torque, Nm 16

