

MSBCCL100LA-8 0,75KW 230/400V B34

Three-phase asynchronous brake motor in aluminum

Motor type MSBCCL100LA-8 0,75KW 230/400V B34
Brand BUSCK
Item number B3081005


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	4,26	710
400	0,75	50	2,45	710
460	0,86	60	2,45	852

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Starting torque ratio 1,7
Pull up torque ratio 1,3
Pull out torque ratio 2,1

Efficiency class EFF2
Efficiency, load 100% 66
Painting Standard
Color RAL 9005
Weight kg 0
Sound pressure Lp dB(A) 59
Bearing DE 6206-2Z/C3
Bearing NDE 6206-2Z/C3
Balance grade Normal
Cable entries 1xM20

Brake torque, Nm 32



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no