

MSBCCL132S-8 2,2KW 230/400V B3

Three-phase asynchronous brake motor in aluminum


Motor type MSBCCL132S-8 2,2KW 230/400V B3
Brand BUSCK
Item number B3081321

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	2,2	50	10,37	720
400	2,2	50	5,96	720
460	2,53	60	5,96	864

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Starting torque ratio 2
Pull up torque ratio 1,2
Pull out torque ratio 2

Efficiency class EFF2
Efficiency, load 100% 75
Painting Standard
Color RAL 9005
Weight kg 0
Sound pressure Lp dB(A) 64
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Cable entries 2xM25



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no