

T3AB112MA-4 4KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type T3AB112MA-4 4KW 230/400V B3
Brand BUSCK
Item number B3A41121e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	4	50	13,91	1450
400	4	50	8,0	1450
460	4,6	60	8,0	1740

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	88,6
Insulation class	F	Efficiency, load 75%	88,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	88,2
Max. ambient temp.	40°C	Power fact, load 100%	0,82
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	41,05
Torque, Nm	26,34	Sound pressure Lp dB(A)	65
Starting torque ratio	3,1	Bearing DE	6306-2Z/C3
Pull up torque ratio	2,6	Bearing NDE	6206-2Z/C3
Pull out torque ratio	3,7	Balance grade	Normal
Starting current ratio	8,6	Inertia kgm2	0,01529165
Note	Brake motor IE3	Brake torque, Nm	60

