

T3AB112MB-4 5,5KW 230/400V B3

Three-phase asynchronous brake motor in aluminum

Motor type T3AB112MB-4 5,5KW 230/400V B3
Brand BUSCK
Item number B3A41131e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	5,5	50	17,0	2920
400	5,5	50	9,78	2920
460	6,33	60	9,78	3504

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Starting torque ratio 3,3
Pull up torque ratio 2,9
Pull out torque ratio 4,2
Starting current ratio 11,9

Note Brake motor IE3

Efficiency class IE3
Efficiency, load 100% 89,2
Efficiency, load 75% 89,6
Efficiency, load 50% 89,1
Power fact, load 100% 0,91

Painting Standard
Color RAL 9005
Weight kg 48
Sound pressure Lp dB(A) 78
Bearing DE 6306-2Z/C3
Bearing NDE 6206-2Z/C3
Balance grade Normal
Inertia kgm2 0,009251268

Brake torque, Nm 45

