

SPECIFIC N°: OE063A2Q2305P4U

|                                     |                        |                            |                                |
|-------------------------------------|------------------------|----------------------------|--------------------------------|
| MOTOR PART NR                       | OE063A2Q2305P4U        | CUSTOMER PART NR           | -                              |
| DRAWING NR                          | OE063A2Q2305P4U        | MOTOR TYPE                 | OE063A22305P4U                 |
| Type of winding                     | 3 PHASE 1 SPEED        |                            |                                |
| PROTECTION                          | II 2G Ex dbe IIC T4 Gb | CERTIFICATE                | EPT 17 ATEX 2588X              |
| IP PROTECTION                       | IP65                   | ENVIRONMENT CONDITIONS     | -20 /+50°C Max Altitude: 1000m |
| POLES                               | 2                      | NOMINAL POWER kW           | 0.18<br>0.22                   |
| Nom. Speed rpm                      | 2825<br>3390           | Voltage-Frequency          | 230/400V 50Hz<br>265/460V 60Hz |
| Nom. Current A                      | 1.07/0.62<br>1.07/0.62 | COS $\phi$                 | 0,76<br>0,76                   |
| Duty                                | S1 Continuous Duty     | Direction of Rotation      | BIDIRECTIONAL                  |
| Insulation Class                    | F                      | Mounting IM                | B14                            |
| IEC Frame Size                      | 63                     | Material end Shield/Flange | Aluminium                      |
| Material Terminal Box               | Aluminium              | Material Fan               | PLASTIC Nylon V6               |
| Material Cover Fan                  | Zinc plated steel      | Material shaft             | Steel C43                      |
| DE Bearing Type                     | 6202-ZZ                | NDE Bearing Type           | 6202-ZZ                        |
| Position of terminal box            | TOP                    | Cable gland Type           | N.2 M20x1,5                    |
| Cable gland position (view from DE) | Right                  | Thermal protection         | PTC130                         |
| Painting                            | -                      | Motor Colour               | Not painted motor              |
| Run capacitor $\mu$ F               | -                      | Start capacitor            | -                              |

*In compliance with the EC Directives*

2014/34/UE (ATEX)  
2014/30/UE (EMC)  
2006/42/EC (Machinery)  
2011/65/CE (RoHS II)

*and comply with the following Standards*

EN 60079-0, 1, 7  
EN 60034-1,2,5,6,7,9,12,14,  
IEC60072-1,  
EN 60259

## Overall dimensions

