

MS63C-2 0,37KW 230/400V B14




Three-phase asynchronous motor in aluminum

Motor type MS63C-2 0,37KW 230/400V B14
Brand BUSCK
Item number P3020633TK

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	1,7	2840
400	0,37	50	0,98	2840
460	0,43	60	0,98	3408

Duty	S1	Efficiency, load 100%	69,8
Enclosure	IP55	Efficiency, load 75%	68,5
Insulation class	F	Efficiency, load 50%	62,6
Cooling	IC411 (TEFC)	Power fact, load 100%	0,78
Max. ambient temp.	40°C	Painting	Standard
Min. ambient temp.	-20°C	Color	RAL 9005
Max. temp. rise	80 K	Weight kg	4,7
Max altitude, masl	1000	Sound pressure Lp dB(A)	62
Torque, Nm	1,24	Bearing DE	6201-2Z/C3
Starting torque ratio	2	Bearing NDE	6201-2Z/C3
Pull up torque ratio	1,8	Balance grade	Normal
Pull out torque ratio	2,4	Inertia kgm ²	0,0003
Starting current ratio	5,1	Cable entries	1xM20
Winding protection	Thermocontacts		

Note med termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no