

# T2A71C-2 0,75KW 230/400V B14

## Three-phase asynchronous motor in aluminum

Motor type T2A71C-2 0,75KW 230/400V B14  
Brand BUSCK  
Item number P3020713e




| Voltage V | Power kW | Frequency Hz | Current A | Speed rpm |
|-----------|----------|--------------|-----------|-----------|
| 230       | 0,75     | 50           | 3,13      | 2810      |
| 400       | 0,75     | 50           | 1,8       | 2810      |
| 460       | 0,86     | 60           | 1,8       | 3372      |

Duty S1  
Enclosure IP55  
Insulation class F  
Cooling IC411 (TEFC)  
Max. ambient temp. 40°C  
Min. ambient temp. -20°C  
Max. temp. rise 80 K  
Max altitude, masl 1000

Torque, Nm 2,5  
Starting torque ratio 2,2  
Starting current ratio 5,7

Efficiency class IE2  
Efficiency, load 100% 77,4  
Efficiency, load 75% 77,5  
Efficiency, load 50% 74,8  
Power fact, load 100% 0,79

Painting Standard  
Color RAL 9005  
Weight kg 7,1  
Sound pressure Lp dB(A) 65  
Bearing DE 6204-2Z/C3  
Bearing NDE 6204-2Z/C3  
Balance grade Normal  
Cable entries 1xM20



**BUSCK**  
www.busck.eu

Busck & Co AB  
Gamla Riksvägen 14  
428 32 Göteborg  
Sweden  
556027-1990  
info@busck.se

Busck & Co ApS  
Postboks 108  
0900 København C  
Denmark  
info@busck.eu

Busck AS  
Skibåsen 35C  
4636 Kristiansand  
Norway  
info@busck.no