

T3A71C-2 0,75KW 230/400V B35


Three-phase asynchronous motor in aluminum

Motor type T3A71C-2 0,75KW 230/400V B35
Brand BUSCK
Item number P3020714

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	2,85	2870
400	0,75	50	1,64	2870
460	0,86	60	1,64	3444

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	80,7
Insulation class	F	Efficiency, load 75%	80,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	78,2
Max. ambient temp.	40°C	Power fact, load 100%	0,82
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	7,1
Torque, Nm	2,5	Sound pressure Lp dB(A)	65
Starting torque ratio	3	Bearing DE	6202 2RZ C3
Pull up torque ratio	2,2	Bearing NDE	6202 2RZ C3
Pull out torque ratio	3,2	Balance grade	Normal
Starting current ratio	7,1	Inertia kgm ²	0,000606
Winding protection	Thermocontacts	Cable entries	1xM20

Note IE3, Termokontakter



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no