

MS80C-4 1,1KW 230/400V B3

Three-phase asynchronous motor in aluminum

Motor type MS80C-4 1,1KW 230/400V B3
Brand BUSCK
Item number P3040801TK


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	4,43	1430
400	1,1	50	2,55	1430
460	1,27	60	2,55	1716

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,35
Starting torque ratio 3
Pull up torque ratio 2,6
Pull out torque ratio 3,1
Starting current ratio 6,6
Winding protection Thermocontacts

Efficiency class IE2
Efficiency, load 100% 84,1
Efficiency, load 75% 84,9
Efficiency, load 50% 83,7
Power fact, load 100% 0,74

Painting Standard
Color RAL 9005
Weight kg 11
Sound pressure Lp dB(A) 61
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm² 0,002998
Cable entries 1xM20



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no