

T2A112L-4 5,5KW 400/690V B3


Three-phase asynchronous motor in aluminum

Motor type T2A112L-4 5,5KW 400/690V B3
Brand BUSCK
Item number P3041121e

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	11,4	1445
690	5,5	50	6,56	1445
460	6,33	60	11,4	1734

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	87,7
Insulation class	F	Efficiency, load 75%	88,1
Cooling	IC411 (TEFC)	Efficiency, load 50%	87,5
Max. ambient temp.	40°C	Power fact, load 100%	0,80
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	35
Torque, Nm	36	Sound pressure Lp dB(A)	65
Starting torque ratio	3,8	Bearing DE	6306-2Z/C3
Pull up torque ratio	3,2	Bearing NDE	6206-2Z/C3
Pull out torque ratio	3,6	Balance grade	Normal
Starting current ratio	8,3	Cable entries	2xM25, 1xM16

Note IE2



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no