


ZWE280MB-4 110KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type ZWE280MB-4 110KW 400/690V B3
Brand BUSCK
Item number P3042801

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	110	50	191,0	1485
690	110	50	109,8	1485
460	126,5	60	191,0	1782

Duty	S1	Efficiency class	IE2
Enclosure	IP55	Efficiency, load 100%	94,8
Insulation class	F	Efficiency, load 75%	94,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	93,4
Max. ambient temp.	40°C	Power fact, load 100%	0,87
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	650
Torque, Nm	707,4	Sound pressure Lp dB(A)	68
Starting torque ratio	2,2	Bearing DE	6317
Starting current ratio	7,2	Bearing NDE	6314
Winding protection	Thermistors	Balance grade	Normal
		Cable entries	2xM63 + 1xM16
Note	IE2		



A	B	B1	C	H	D	E	F	G	DH	GA	AA	AB	AC	HA	HD	BB	LD	L
457	419		190	280	75	140	20	67.5	M20	79.5	85	542	550	35	681	490	361	1020