

MS71C-6 0,37KW 230/400V B3

Three-phase asynchronous motor in aluminum

Motor type MS71C-6 0,37KW 230/400V B3
Brand BUSCK
Item number P3060711


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,37	50	2,21	890
400	0,37	50	1,27	890
460	0,43	60	1,27	1068

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 3,97
Starting torque ratio 2,0
Pull up torque ratio 1,5
Pull out torque ratio 2,1
Starting current ratio 4

Efficiency, load 100% 61
Efficiency, load 75% 60
Efficiency, load 50% 53
Power fact, load 100% 0,69

Painting Standard
Color RAL 9005
Weight kg 6,8
Sound pressure Lp dB(A) 54
Bearing DE 6202-2Z/C3
Bearing NDE 6202-2Z/C3
Balance grade Normal
Inertia kgm² 0,00115
Cable entries 1xM20



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no