

MS90L-2 2,2KW 230/400V B3 ATEX ZON 2/22




Three-phase asynchronous motor in aluminum

Motor type MS90L-2 2,2KW 230/400V B3 ATEX ZON 2/22
Brand BUSCK
Item number Q3020911

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	2,2	50	8,02	2840
400	2,2	50	4,61	2840
460	2,53	60	4,61	3408

Duty	S1	Efficiency class	IE1
Enclosure	IP65	Efficiency, load 100%	81
Insulation class	F	Power fact, load 100%	0,85
Cooling	IC411 (TEFC)	Painting	Standard
Max. ambient temp.	40°C	Color	RAL 9005
Min. ambient temp.	-20°C	Weight kg	14,5
Max. temp. rise	80 K	Sound pressure Lp dB(A)	72
Max altitude, masl	1000	Bearing DE	6205-2Z/C3
		Bearing NDE	6205-2Z/C3
Torque, Nm	7,4	Balance grade	Normal
Starting torque ratio	2,2	Inertia kgm ²	0,0017
Pull up torque ratio	1,4	Cable entries	Metal cable gland 1xM20
Pull out torque ratio	2,4		
Starting current ratio	6		

Note ATEX II 3 D Ex tc IIIC T125°C Dc ZONE 22
ATEX II 3 G Ex nA IIC T4 Gc ZONE 2
IP65, Termistorer



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no