




T3W180L-4 22KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type T3W180L-4 22KW 400/690V B3
 Brand BUSCK
 Item number V3041811TS

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	39,3	1460
690	22	50	22,6	1460
460	25,3	60	39,3	1752

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	93
Insulation class	H	Efficiency, load 75%	93,7
Cooling	IC418 (Non ventilated)	Efficiency, load 50%	92,9
Max. ambient temp.	90°C	Power fact, load 100%	0,87
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	195
Torque, Nm	144	Sound pressure Lp dB(A)	76
Starting torque ratio	2,5	Bearing DE	6311 C4
Winding protection	PTC 180°C	Bearing NDE	6311 C4
		Grease	Mobil Mobilith SHC200
		Balance grade	Normal
Note	Speedi sleeve	Inertia kgm2	0,194
	Internal tropicalization	Cable entries	2xM32, 1xM12



TC 180L B3

BUSCK
 www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
 info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
 info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
 info@busck.no