




T3W160L-6 11KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type T3W160L-6 11KW 400/690V B3
 Brand BUSCK
 Item number V3061611TS

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	11	50	23,1	960
690	11	50	13,31	960
460	12,65	60	23,1	1152

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	90,3
Insulation class	H	Efficiency, load 75%	91,2
Cooling	IC418 (Non ventilated)	Efficiency, load 50%	88,5
Max. ambient temp.	90°C	Power fact, load 100%	0,76
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	139
Torque, Nm	109	Sound pressure Lp dB(A)	73
Starting torque ratio	2,5	Bearing DE	6309 C4
Starting current ratio	8,5	Bearing NDE	6309 C4
Winding protection	PTC 180°C	Grease	Mobil Mobilith SHC200
		Balance grade	Normal
		Inertia kgm ²	0,135
Note	Speedi sleeve	Cable entries	2xM32, 1xM12
	Internal tropicalization		



TC 160L B3

BUSCK
www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
info@busck.no