

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron flameproof**

www.tamel.pl

Produced by **Tamel S.A.** a company of



Motor type: **W-UEF315MNE 4P 132KW Ex d**
Motor item number:

Rated power:	132 kW	50 HZ data	60 HZ data
Poles(Synch speed):	4p (1500) r.p.m		
Full load speed:	1480 r.p.m		
Voltage:	380-415 V		
Frequency:	50 Hz		
Connection:	Y / Δ		
Amps full load (FLA):	A		
Amps no-load (NLA):	A		

Enclosure:	IP55	Cable entries size:	1 x CM50 + 1 x CM20
Mounting:		Winding protection:	
Insulation Class:	F /	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	no
Min. ambient temp.:	-20 °C	Shaft extension:	80x170 mm
Max. temp. rise:	80 K	Weight:	1240 kg
Duty type:	S1	Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6319 C3	Box position:	Top DE
Bearing NDE	6319 C3	Cable entry towards:	Right
Grease:	Esso Unirex N3	Cable type:	N/A
Regreasing facilities:	YES	Balance grade:	Reduced

Efficiency class:		Sound pressure (1m):	71 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,027 PH
Efficiency:	95,8 95,6 94,2		
Power factor:	0,87 0,85 0,77		

Full load torque (FLT):	852 Nm	Pull out torque ratio:	2,6 MK/MN
Starting torque ratio:	2,4 MA/MN	Pull up torque:	2,0 MS/MN
Starting current ratio:	7,7 IA/IN	Rotor inertia WK2:	3,7 kgm²

Special remarks:
PTC 150 °C

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification: Ex db eb IIB	Temp. Class: T4
Certificate number: BAS02ATEX2121X	t _E time: sek

Special remarks:
