

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DA160LV IE3 6P 11kW
Motor item number:

Rated power:	11	kW			12,7	kW
Poles(Synch speed):	6p (1000)	r.p.m			6p (1200)	r.p.m
Full load speed:	980	r.p.m			1175	r.p.m
Voltage:	230 / 400	V			460	V
Frequency:	50	Hz			60	Hz
Connection:	Δ / Y				Δ	
Amps full load (FLA):	40,5 / 23,4	A			22,9	A
Amps no-load (NLA):		A				A

Enclosure:	IP55			Cable entries size:	2 x CM32
Mounting:				Winding protection:	NO
Insulation Class:	F			Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40	°C		Heater:	NO
Min. ambient temp.:		°C		Shaft extension:	42x110 mm
Max. temp. rise:	80	°C		Weight:	92 kg
Duty type:	S1			Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)			Color:	RAL 5021
Bearing DE	6309	ZZ C3		Box position:	Top DE
Bearing NDE	6307	ZZ C3		Cable entry towards:	Right
Grease:	Esso Unirex N3			Cable type:	N/A
Regreasing facilities:	NO			Balance grade:	Normal

Efficiency class:	IE3		
Load data:	100%	75%	50%
Efficiency:	90,3	90,3	90
Power factor:	0,75	0,69	0,59

Sound pressure (1m): 59 dB(A)
Resistance R20: 0,728 PH

Full load torque (FLT):	107	Nm		Pull out torque ratio:	2,5	MK/MN
Starting torque ratio:	2,0	MA/MN		Pull up torque:	1,9	MS/MN
Starting current ratio:	5,7	IA/IN		Rotor inertia WK2:	0,12	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: