

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DA160MJ IE3 2P 11kW
Motor item number:

Rated power:	11	kW				12,6	kW
Poles(Synch speed):	2p (3000)	r.p.m				2p (3600)	r.p.m
Full load speed:	2945	r.p.m				3545	r.p.m
Voltage:	230 / 400	V				460	V
Frequency:	50	Hz				60	Hz
Connection:	Δ / Y					Δ	
Amps full load (FLA):	33,9 / 19,6	A				19	A
Amps no-load (NLA):		A					A

Enclosure:	IP55					Cable entries size:	2 x CM32
Mounting:						Winding protection:	NO
Insulation Class:	F					Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	40	°C				Heater:	NO
Min. ambient temp.:	-20	°C				Shaft extension:	42x110 mm
Max. temp. rise:	80	°C				Weight:	73 kg
Duty type:	S1					Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)					Color:	RAL 5021
Bearing DE	6309	ZZ C3				Box position:	Top DE
Bearing NDE	6307	ZZ C3				Cable entry towards:	Right
Grease:	Esso Unirex N3					Cable type:	N/A
Regreasing facilities:	NO					Balance grade:	Normal

Efficiency class:	IE3					Sound pressure (1m):	68 dB(A)
Load data:	100%	75%	50%			Resistance R20:	0,727 PH
Efficiency:	92,2	92,5	91,5				
Power factor:	0,88	0,85	0,77				

Full load torque (FLT):	36	Nm				Pull out torque ratio:	3,6	MK/MN
Starting torque ratio:	3,6	MA/MN				Pull up torque:	1,8	MS/MN
Starting current ratio:	7,6	IA/IN				Rotor inertia WK2:	0,045	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:		Temp. Class:	
Certificate number:		t _E time:	sek

Special remarks: