

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type:

WP-DA160MR IE3 2P 15kW

Motor item number:

Rated power:	15	kW				17,3	kW
Poles(Synch speed):	2p (3000)	r.p.m				2p (3600)	r.p.m
Full load speed:	2940	r.p.m				3565	r.p.m
Voltage:	400 / 690	V				460	V
Frequency:	50	Hz				60	Hz
Connection:	Δ / Y					Δ	
Amps full load (FLA):	26 / 15	A				25,7	A
Amps no-load (NLA):		A					A

Enclosure:	IP55					Cable entries size:	2 x CM32
Mounting:						Winding protection:	NO
Insulation Class:	F					Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	40	°C				Heater:	NO
Min. ambient temp.:	-20	°C				Shaft extension:	42x110 mm
Max. temp. rise:	80	°C				Weight:	80 kg
Duty type:	S1					Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)					Color:	RAL 5021
Bearing DE	6309	ZZ C3				Box position:	Top DE
Bearing NDE	6307	ZZ C3				Cable entry towards:	Right
Grease:	Esso Unirex N3					Cable type:	N/A
Regreasing facilities:	NO					Balance grade:	Normal

Efficiency class:	IE3			
Load data:	100%	75%	50%	
Efficiency:	93	93,3	93,1	
Power factor:	0,90	0,87	0,79	

Sound pressure (1m): 0,056 dB(A)
Resistance R20: 0,534 PH

Full load torque (FLT):	49	Nm			Pull out torque ratio:	3,7	MK/MN
Starting torque ratio:	2,2	MA/MN			Pull up torque:	1,9	MS/MN
Starting current ratio:	8,6	IA/IN			Rotor inertia WK2:	0,056	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:		Temp. Class:	
Certificate number:		t _E time:	sek

Special remarks: