

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type:

WP-DA160MR IE3 4P 11kW

Motor item number:

Rated power:	11	kW				12,6	kW
Poles(Synch speed):	4p (1500)	r.p.m				4p (1800)	r.p.m
Full load speed:	1475	r.p.m				1775	r.p.m
Voltage:	230 / 400	V				460	V
Frequency:	50	Hz				60	Hz
Connection:	Δ / Y					Δ	
Amps full load (FLA):	36,2 / 20,9	A				21,5	A
Amps no-load (NLA):		A					A

Enclosure:	IP55					Cable entries size:	2 x CM32
Mounting:						Winding protection:	NO
Insulation Class:	F					Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40	°C				Heater:	NO
Min. ambient temp.:	-20	°C				Shaft extension:	42x110 mm
Max. temp. rise:	80	°C				Weight:	88 kg
Duty type:	S1					Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)					Color:	RAL 5021
Bearing DE	6309	ZZ C3				Box position:	Top DE
Bearing NDE	6307	ZZ C3				Cable entry towards:	Right
Grease:	Esso Unirex N3					Cable type:	N/A
Regreasing facilities:	NO					Balance grade:	Normal

Efficiency class:	IE3					Sound pressure (1m):	63 dB(A)
Load data:	100%	75%	50%			Resistance R20:	0,695 PH
Efficiency:	92,5	92,8	92				
Power factor:	0,82	0,75	0,62				

Full load torque (FLT):	71	Nm				Pull out torque ratio:	3,7	MK/MN
Starting torque ratio:	3,0	MA/MN				Pull up torque:	2,4	MS/MN
Starting current ratio:	9,0	IA/IN				Rotor inertia WK2:	0,084	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:		Temp. Class:	
Certificate number:		t _E time:	sek

Special remarks: