

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DA180LM IE3 4P 22kW
Motor item number:

50 HZ data	Rated power:	22	kW	60 HZ data	25,3	kW
	Poles(Synch speed):	4p (1500)	r.p.m		4p (1800)	r.p.m
	Full load speed:	1470	r.p.m		1775	r.p.m
	Voltage:	230 / 400	V		460	V
	Frequency:	50	Hz		60	Hz
	Connection:	Δ / Y			Δ	
	Amps full load (FLA):	71,2 / 41,1	A		40,3	A
	Amps no-load (NLA):		A			A

Enclosure:	IP55	Cable entries size:	2 x CM32
Mounting:		Winding protection:	NO
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	NO
Min. ambient temp.:	°C	Shaft extension:	48x110 mm
Max. temp. rise:	80 °C	Weight:	126 kg
Duty type:	S1	Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6310 ZZ C3	Box position:	Top DE
Bearing NDE	6308 ZZ C3	Cable entry towards:	Right
Grease:	Esso Unirex N3	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE3	Sound pressure (1m):	62 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,292 PH
Efficiency:	93 93 93		
Power factor:	0,83 0,75 0,62		

Full load torque (FLT):	143 Nm	Pull out torque ratio:	3,0 MK/MN
Starting torque ratio:	3,1 MA/MN	Pull up torque:	2,0 MS/MN
Starting current ratio:	8,8 IA/IN	Rotor inertia WK2:	0,17 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: