

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DF160LV IE3 6p 11,0kW
Motor item number:

Rated power:	11	kW	50 HZ data	12,7	kW	60 HZ data
Poles(Synch speed):	6p (1000)	r.p.m		6p (1200)	r.p.m	
Full load speed:	980	r.p.m		1175	r.p.m	
Voltage:	400 / 690	V		460	V	
Frequency:	50	Hz		60	Hz	
Connection:	Δ / Y			Δ		
Amps full load (FLA):	23,4 / 13,6	A		22,9	A	
Amps no-load (NLA):		A			A	

Enclosure:	IP55	Cable entries size:	2 x M32
Mounting:	IM B3 (IM 1001)	Winding protection:	NO
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	NO
Min. ambient temp.:	-20 °C	Shaft extension:	42x110 mm
Max. temp. rise:	80 °C	Weight:	133 kg
Duty type:	S1	Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE		Box position:	Top DE
Bearing NDE		Cable entry towards:	Right
Grease:	Esso Unirex N3	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE3	Sound pressure (1m):	59 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,728 PH
Efficiency:	90,3 90,3 90		
Power factor:	0,75 0,69 0,53		

Full load torque (FLT):	107 Nm	Pull out torque ratio:	2,8 MK/MN
Starting torque ratio:	2,0 MA/MN	Pull up torque:	1,9 MS/MN
Starting current ratio:	5,7 IA/IN	Rotor inertia WK2:	0,12 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: