

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron**

Motor type: **WP-UDF200LNX IE3 2P 30kW**
Motor item number:

Rated power:	30	kW	34,5	kW
Poles(Synch speed):	2p (3000)	r.p.m	2p (3600)	r.p.m
Full load speed:	2945	r.p.m	3545	r.p.m
Voltage:	400 / 690	V	460	V
Frequency:	50	Hz	60	Hz
Connection:	Δ / Y		Δ	
Amps full load (FLA):	53 / 30,5	A	53	A
Amps no-load (NLA):		A		A

Enclosure:	IP55	Cable entries size:	2xM32 + 1xM20
Mounting:		Winding protection:	3x PTC 160 °C
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	NO
Min. ambient temp.:	-20 °C	Shaft extension:	55x110 mm
Max. temp. rise:	80 °C	Weight:	255 kg
Duty type:	S1	Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021 Argus
Bearing DE	6312 C3	Box position:	Top DE
Bearing NDE	6312 C3	Cable entry towards:	Right
Grease:	NSK EA6	Cable type:	EXAR 500 6 mm ²
Regreasing facilities:	YES	Balance grade:	Normal

Efficiency class:	IE3	Sound pressure (1m):	73 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,173 PH
Efficiency:	93,3 93,3 93		
Power factor:	0,88 0,85 0,78		

Full load torque (FLT):	97 Nm	Pull out torque ratio:	3,0 MK/MN
Starting torque ratio:	2,8 MA/MN	Pull up torque:	2,4 MS/MN
Starting current ratio:	9,0 IA/IN	Rotor inertia WK2:	0,15 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: