

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron**

Motor type: **WP-UDF355SN IE3 4P 280kW**
Motor item number:

50 HZ data	Rated power:	280	kW	60 HZ data	320	kW
	Poles(Synch speed):	4p (1500)	r.p.m		4p (1800)	r.p.m
	Full load speed:	1490	r.p.m		1790	r.p.m
	Voltage:	400 / 690	V		460	V
	Frequency:	50	Hz		60	Hz
	Connection:	Δ / Y			Δ	
	Amps full load (FLA):	478 / 277	A		474	A
	Amps no-load (NLA):		A			A

Enclosure:	IP55	Cable entries size:	2 x M63 + 1 x M20
Mounting:		Winding protection:	3xPTC160
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	40 °C	Heater:	no
Min. ambient temp.:	-20 °C	Shaft extension:	100x210 mm
Max. temp. rise:	80 °C	Weight:	2100 kg
Duty type:	S1	Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)	Color:	RAL 5021 Argus
Bearing DE	N324 C3	Box position:	Top DE
Bearing NDE	6324 C3	Cable entry towards:	Right
Grease:	NSK EA6	Cable type:	ZYRAD500 25mm2
Regreasing facilities:	YES	Balance grade:	Normal

Efficiency class:	IE3	Sound pressure (1m):	76 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,008 PH
Efficiency:	96 96 95,5		
Power factor:	0,88 0,86 0,80		

Full load torque (FLT):	1795 Nm	Pull out torque ratio:	2,5 MK/MN
Starting torque ratio:	2,1 MA/MN	Pull up torque:	1,7 MS/MN
Starting current ratio:	7,2 IA/IN	Rotor inertia WK2:	10,6 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: