



TECHNICAL DATA SHEET

Document signed at: 2020.5.22	Document No.
-------------------------------	--------------

Three- phase synchronous motors

Motor type	Power(kW)	Vdrive(V)	Hz	Poles	Enclosure
WST112-1800-7.5	7.5	400	90	6	IC411

Nameplate Details

Rated Current(A)	Rated Speed(rpm)	Insulation Class	Protection	Duty class	Mounting
14.9	1800	F	IP55	S1	B3/B5/B14/B35/B34
At 20℃ BEMF(V)	Efficiency(%)	Ambient Temperature(℃)		Weight(kg)	Ref.serial number
288	93,4	40		34	
Bearing Type(DE)	6306-2Z/C3			Bearing Type (NDE)	6205-2Z/C3

Load Charactersitics Data

Load (%)	25%	50%	75%	100%	Torque and Current Figures(F.L)	
Current (A)	4,2	7,84	11,4	14.9	Peak torque ratio	2,4
Efficiency(%)	85,3	90,9	95,6	93,4	Peak current ratio	2,6
Power Factor						

Factory pre-delivery test

No Load Test						
Amps(A)	Watts(W)	BEMF(V)				
0,43	292	288				

Additional Information

L_d(mH)	4,85	L_q(mH)	13,02
Vibration(p-p)-mm/s	1,6	Noise Level-dB(A)	69
Temperature Rise(Class)	45K	Winding Resistance(Phase Ends)	0.208Ω

Options
