

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: Aluminium

Motor type: WP-DA132MVX IE3 5.5KW 6P B3
Motor item number: 132W328602T

Rated power:	5,5	kW			6,3	kW
Poles(Synch speed):	6p (1000)	r.p.m			6p (1200)	r.p.m
Full load speed:	965	r.p.m			1160	r.p.m
Voltage:	400 / 690	V			460	V
Frequency:	50	Hz			60	Hz
Connection:	Δ / Y				Δ	
Amps full load (FLA):	13,3 / 7,7	A			12,4	A
Amps no-load (NLA):		A				A

Enclosure:	IP55				Cable entries size:	2xCM25
Mounting:	IM B3 (IM 1001)				Winding protection:	NO
Insulation Class:	F				Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40	°C			Heater:	NO
Min. ambient temp.:	-20	°C			Shaft extension:	38x80 mm
Max. temp. rise:	80	°C			Weight:	60,5 kg
Duty type:	S1				Painting:	Manufacturer standard
Cooling form:	IC411 (TEFC)				Color:	RAL 5021
Bearing DE	6208	ZZ C3			Box position:	Top DE
Bearing NDE	6305	ZZ C3			Cable entry towards:	Right
Grease:	Esso Unirex N3				Cable type:	N/A
Regreasing facilities:	NO				Balance grade:	Normal

Efficiency class:	IE3				Sound pressure (1m):	58 dB(A)
Load data:	100%	75%	50%		Resistance R20:	1,6 PH
Efficiency:	88	87	84			
Power factor:	0,68	0,53	0,42			

Full load torque (FLT):	54	Nm			Pull out torque ratio:	3,0	MK/MN
Starting torque ratio:	2,6	MA/MN			Pull up torque:	1,9	MS/MN
Starting current ratio:	6,5	IA/IN			Rotor inertia WK2:	0,0414	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:		Temp. Class:	
Certificate number:		t _E time:	sek

Special remarks: